

V226Wa



- 21.5" Wide LCD TFT
- Full HD 1080p
- 1920 x 1080 Resolution
- 20000:1 Dynamic contrast
- Brightness 300cd/m²
- 5 ms Response time
- Analog D-Sub



The ideal monitor for EDV workplaces, at home and in the office. The V226Wa unites the newest technology and design with an optimal price-performance ratio.

- Excellent Design : Glossy Black Elegant Design
- Full HD 1920x1080 resolution and 20,000:1 dynamic contrast ratio
- No ghosting-effect thanks to 5 ms response time
- sharp, brilliant pictures by high contrast and brightness.

Technical Specifications

V226Wa



Panel Technology	LCD	A-Si TFT Active Matrix / TN
Panel Specifications	Size (Diagonal)	21.5" / 54.7cm
	Aspect Ratio	16:9
	Active Display Size	477.504x268.596 mm (H x V)
	Pixel Pitch	0.248 mm (HxV)
	Viewing Angle	170° / 160° (CR≥ 10)
	Contrast Ratio	20000:1 (Dynamic Contrast)
	Response Time	5ms
	Luminance	300 cd/m ² (Typical)
	Display Color	16.7M
	Scanning Frequency	Horizontal
Vertical		56 ~ 75 Hz
Resolution	Maximal	1920 x 1080 @ 60Hz
	Recommended	1920 x 1080 @ 60Hz
	Preset / Analog	640x480@60/75Hz, 800x600@60/75Hz, 1024x768@60/75Hz, 1280x1024@60/75Hz 1440 x 900@59.9/60Hz, 1680 x 1050@60Hz, 1920 x 1080@60Hz
Input Signal	Video	RGB Analog
	Synchronization	H/V-Separate
Connectors	Analog	15-pin D-Sub Audio: Ø3.5mm Jack
	Cable Size	1.5 m
Plug-and-Play		VESA DCC CI
Lifespan (MTBF)	Panel / Backlight	50,000 Operating Hours
Power Management		VESA DPMS
Power Supply System	Voltage	100 ~ 240V AC 1.0A
	Consumption(Typ.)	50W (Max)
Power Supply		Internal
Safety & Regulations		KCC, VCCI, UL, CB, TUV-GS, FCC, CE, RoHS, WEEE, Energy Star
Other features	Audio System	Internal Loudspeaker 2ch x 1 Watt
	Kensington Security Slot	Yes
	Compatible with	VESA Standard / 100 x 100 mm
Stand	downtilt	-5° / 25°
Cabinet Color		Glossy Black
Dimension(W x H x D)	Unit / Packed	512.7 x 366.1 x181.4mm / 575 x 374 x 131mm
	Weight	4.3 kg / 6.8 kg
Scope of Deliver		Power cable, D-Sub Cable, Audio Cables, Quick Guide
		CD-ROM : User Manual, Driver, ICM profile,
EAN Code		880 909 374 585 8

Technical details are subject to change without further notice. Errors excepted. Version : as of June 2009.

HYUNDAI IT EUROPE GmbH

Geheimrat-Hummel-Platz 2, 65239 Hochheim Germany

Tel: +49 (0) 6146-904-0 Fax. +49 (0) 6146-904-110

E-mail: info@hyundaiit.eu



www.hyundaiIT.com