



X Series

X224W

▶ Key Feature

- VESA Wall Frame Hole: 100 x 100 mm(W X H)
- Kensington lock: Yes
- Audio system: 1W x 2ch
- Stand: Tilt Stand

▶ Specification

Display Panel	Screen size	22 inch Wide
	Type	A-Si TFT Active Matrix
	Viewing Angle(H/V)	170/ 160(CR≥10)
	Pixel Pitch	0.282 mm (H x V)
	Resolution	1680 x 1050
	Response Time(ms)	5ms
	Contrast Ratio	1000:1
	Brightness	300 cd/m ²
Signal Input	Active Display Size(H x V)	473.8 x 296.1 mm
	Display Color	16.7 Million
	Video	R.G.B Analog Digital Signal
	Sync	H/V - Separate TMDS Signal
	Connector	15 pin D-sub DVI-D Connector(Option) Audio: Ø3.5mm Jack
	Cable	
	Horizontal	31.5 ~ 83kHz
	Vertical	56 ~ 76Hz
Scanning Frequency		
Max. Resolution (Analog)		1680 x 1050 @ 60Hz
Recommended Resolution		1680 x 1050 @ 60Hz
Plug-and-Play		VESA DDC/ CI
Features	VESA Wall Frame Hole	100 x 100 mm(W X H)
	Kensington lock	Yes
	Audio system	1W x 2ch
	USB Hub	
	Stand	Tilt Stand
	Option	
Power Management		VESA DPMS
Power	Source	100-240V AC 2.2A
	Consumption	55W(Max)
	Type	Built-in
Emmissions Standard		TCO'03
Safety & Regulations	Standard	Nemko/GS, UL/CUL, CB Energy Star, EK,GOST VCCI, FCC, CE, WEEE
Dimension (W x H x D)	Unit	510 x 421.2 x 227.6 mm
	Packed	569 x 481 x 130 mm
Weight	Unit	4.9 kg
	Packed	6.7 kg
Loading Q'ty	20 ft. Container	768 PCS
	40 ft. Container	1536 PCS
UPC Code		

All specifications are subject to change without prior notice

www.hyundaiit.com